

Name of Driver		Date	Track		Engine	Plug	Muffler	
Reno Savoya		23/08/20	Quinta Las Tulipas Flat High grip		Picco P3TT	Picco #5	Picco 2166	
Spur Gear		Clutch Bell	Clutch Spring	Clutch Shoe	Tire	Tire Insert	Wheel	Body
46 T		☐ Std. ☒ LW 13T	☐ 0.90 ☐ 1.00 ☒ 0.95 ☐ 1.10	Carbon ☒ Aluminum ☒ 3	Tire : Catapult Compounds: MLW	AKA red	AKA	stock
								Fuel
								Hot road GT

Diff. Gear Set-Up

	Front	Center	Rear
Diff. Gear	☒ Std. ☐ LSD	☒ Std. ☐ LSD	☒ Std. ☐ LSD
Ring Gear	☒ 43/13 ☐ 42/12	# 20k	☒ 43/13 ☐ 42/12
	# 20k		# 5k

Shock Set-Up

	Front	Rear
Shock Type	P : w/Diaphragm A : Aeration	Size type P - stock
Shock Piston	B : Black W : White T : Taper	Size type W φ 1,3 x 8
Shock Oil	# 550	# 800
Shock Spring	Grey (IF350-6514)	Red (IFW607-8515)

Ride Height

Front	Rear
23 mm	28 mm

Rebound

Front	Rear
102 mm	119 mm

Camber Angle

Front	Rear
+ -2 °	+ -2 °

Toe Angle

Front	Rear
+ -2 °	☒ 2.5° ☐ 3° ☐ 3.5°

Wheelbase

Collar of Rear Hub	Front Side 3 mm Rear Side 2 mm
--------------------	-----------------------------------

Shock Mount Position

<Front>	<Rear>	Rear Upper Shock Bush
☐ ☒ ☐	☒ ☐ ☐	☐ Std. ☒ Long
		Sus. Arm
		Front ☐ In ☒ Out
		Rear ☐ In ☒ Out

Rear Upper Arm Position

☐ Plastic ☒ Aluminum	Hub Carrier Bush
	☒ Plastic ☐ Brass
☐ Narrow ☒ Std. ☐ Wide	


Front Sus. Arm

☐ Soft (Std.)	☒ Hard
--------------------------------------	--

Front Sus. Bush

Rear Side	☒ ☐ ☐
-----------	---

Front Upper Arm Position




Front Wheel Hub

☐ Narrow ☒ Std. ☐ Wide
--

Front Hub Carrier

☐ Plastic ☒ Aluminum
☐ 13° ☐ 16° ☒ 17.5° ☐ 19°



Rear Sus. Bush

Front Side	☐ ☒ ☐ ☐
Rear Side	☒ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐


Rear Sus. Arm

☐ Soft (Std.)	☒ Hard
Rear Sus. Bush	
☐ Short	☐
☐ Medium	☐
☒ Long	☐

Servo Horn

Steering	Throttle
☐ Plastic	☐ Plastic
☒ AL. Long	☒ AL.
☐ AL. Short	

Steering Plate



Sway Bar

Front	Rear
φ 2,4mm	φ 2,7mm
1 mm	1 mm

Weight

Front	Rear
☐ None	☒ None
☐ IFW604-10	☐ IFW605-10
☒ IFW604-20	☐ IFW605-20
☐ other	☐ other

Wing

☒ IF491(TK14)	Flap ☒ None
	☐ 5mm
	☐ 8mm
	☒ Holes

memo:

Options on setup sheet plus:

- titanium screws IFW602
- aluminum diff pins IFW467
- aluminum AMB plate IFW426
- rear center dogbone IFW616 and IFW617
- IFW52B clutch shoes