

Name of Driver		Date	Track		Engine	Plug		Muffler	
Reno Savoya		04/2021	Basic		Picco P3TT	Picco P5TH		EFRA 2166	
				Condition: 20°C					
Spur Gear	Clutch Bell	Clutch Spring		Clutch Shoe	Tire	Tire Insert	Wheel	Body	Fuel
45 T	☐ Std. ☒ LW	☐ 0.90 ☐ 1.00	Carbon ☒	Tire : AKA Impact	AKA	Stock	TKI2		Hot Road G
	13 T	☒ 0.95 ☐ 1.10	Aluminum ☒ 3	Compounds: SLW					

● Diff. Gear Set-Up

	Front	Center	Rear
Diff. Gear	☒ 10/20 ☐ 12/18 ☐ LSD	☒ 10/20 ☐ 12/18 ☐ LSD	☒ 10/20 ☐ 12/18 ☐ LSD
Ring Gear	☒ 43/13 ☐ 42/12	# 7 000	☒ 43/13 ☐ 42/12
	# 7 000	# 7 000	# 3 000

● Shock Set-Up

	Front	Rear
Shock Type	P : w/Diaphragm A : Aeration	Size TKI2 50mm type P
Shock Piston	B : Black W : White T : Taper	Size TKI2 58mm type P
Shock Oil	# 800	# 700
Shock Spring	Grey (78mm)	Grey (95mm)

● Ride Height

Front	Rear
23 mm	27 mm

● Rebound

Front	Rear
109 mm	124 mm

● Camber Angle

Front	Rear
+ 2°	+ 2°


● Toe Angle

Front	Rear
+ 2°	☒ 2.5° ☐ 3° ☐ 3.5°

● Wheelbase

Collar of Rear Hub	Front Side 5 mm Rear Side 0 mm
--------------------	-----------------------------------

● Shock Mount Position



Shock Stay

Front	☐ Short ☒ Long
Rear	☐ Short ☒ Long


Rear Upper Shock Bush

☐ Std. ☒ Long
--

Sus. Arm

Front	☐ In ☒ Out
Rear	☐ In ☒ Out

● Rear Upper Arm Position



☐ Plastic ☒ Aluminum
--

Hub Carrier Bush

☒ Plastic ☐ Brass

● Rear Wheel Hub

☐ Narrow ☐ Std. ☒ Wide
--


● Front Sus. Arm

☒ Soft (Std.) ☐ Hard

● Front Sus. Bush

Rear Side	☐ ☐ ☒
-----------	---

● Front Upper Arm Position




● Front Wheel Hub

☐ Narrow ☒ Std. ☐ Wide
--

● Front Hub Carrier

☐ Plastic ☒ Aluminum
☐ 13° ☐ 16° ☒ 17.5° ☐ 19°



● Rear Sus. Bush

Front Side	☒ ☐ ☐ ☐
Rear Side	☒ ☐ ☐ ☐ ☐ ☐ ☐ ☐


● Rear Sus. Arm

☐ Soft (Std.) ☒ Hard
Rear Sus. Bush
☐ Short ☐ Medium ☒ Long


● Servo Horn

Steering	Throttle
☐ Plastic ☒ AL. Long ☐ AL. Short	☐ Plastic ☒ AL.

● Steering Plate



● Sway Bar



Front	Rear
φ 2,3mm	φ 2,7mm
1 mm	1 mm

● Weight

Front	Rear
☐ None ☐ IFW604-10 ☒ IFW604-20 ☐ other	☐ None ☐ IFW605-10 ☒ IFW605-20 ☐ other

● Wing

☒ IF491(TKI4)	Flap ☒ None ☐ 5mm ☐ 8mm ☒ Holes
---	--

memo:

Basic setup everywhere I go it works ! :-)

Options:
IFW474 17.5 aluminum caster blocks
IFW612
Titanium screws and turnbuckles for weight saving
IFW136 clutch shoes
IFW426 Aluminum AMB plate