Inferno MP10 SET UP SHEET

ver.1.03 KYOSHO

Name of Driver	Date	Track	Engine	Plug	Muffler
Renaud Savoya	24/04/22	TTRC90 Bermont Condition: Wet Temperature: 8°C	Picco P3TT	P5TH	EFRA 2166

Spur Gear	Clutch Bell	Clutch Spring	Clutch Shoe	Tire	Tire Insert	Wheel	Body	Fuel
45 T	☐ Std. ☒ LW 13 T	☐ 0.90 ☐ 1.00 ☒ 0.95 ☐ 1.10	Carbon x Aluminum x 3 IFW136	Tire Gridiron Compounds: Ultrasoft	AKA	AKA	TKI2	Hot Road GT

Diff. Gear Set-Up

	Front	Center	Rear
Diff. Gear	☒ 10/20 ☐ 12/18 ☐ LSD	☒ 10/20 ☐ 12/18 ☐ LSD	☒ 10/20 ☐ 12/18 ☐ LSD
	Ring Gear ☒ 43/13 ☐ 42/12 # 10k	Diff. Size ☒ Small ☐ Large # 7k	Ring Gear ☒ 43/13 ☐ 42/12 # 3k

Shock Set-Up

	Front	Rear
Shock Type (P : w/Diaphragm, A : Aeration)	Size 50 - type P	Size 58 - type P
Shock Piston (B : Black, W : White, T : Taper)	T φ 8 x 1,2	T φ 8 x 1,4
Shock Oil	# 400	# 550
Shock Spring	Red 70mm	Red 81mm

Ride Height

Front	Rear
25 mm	29 mm



Rebound

Front	Rear
107 mm	124 mm



Camber Angle

Front	Rear
± 2 °	± 3 °



Front	Rear
10,3 mm	14,5 mm



Toe Angle

Front	Rear
± 2 °	☒ 2.5° ☐ 3° ☐ 3.5°



30,5 mm

Wheelbase

Collar of Rear Hub	
	Front Side 5 mm
	Rear Side 0 mm

Shock Mount Position



Shock Stay

Front	☐ Short	☒ Long
	☐ Alu	☒ Carbon
Rear	☐ Short	☒ Long
	☐ Alu	☒ Carbon

Sus. Arm

Front	☐ In	☐ Out
Rear	☐ In	☒ Out

Shock Bush

Front	☒ Short	☐ Std.	
Rear	☐ Short	☒ Std.	☐ Long

Rear Upper Arm Position



☐ Plastic
☒ Aluminum

Hub Carrier Bush
☒ Plastic
☐ Brass



Rear Wheel Hub

☒ Narrow ☐ Std. ☐ Wide

Front Sus. Arm

☐ SS ☒ Soft (Std.) ☐ Hard

Front Sus. Bush

Rear Side ☐ ☒

Front Upper Arm Position



Front Wheel Hub

☐ Narrow ☒ Std. ☐ Wide

Front Hub Carrier

☐ Plastic ☒ Aluminum
☐ 13° ☒ 16° ☐ 17.5° ☐ 19° ☐ 22°



Lower Bush ☒ Plastic ☐ Brass
☐ -1° ☒ 0° ☐ +1°

Rear Sus. Bush

Front Side	☐ ☐ ☒ ☐
Rear Side	☒ 2.5 2.5 ☐ 3 3 ☐ 3.5 3.5 ☐ 2.2 2.2 ☐ 3 3 ☐ 3.5 3.5

Rear Sus. Arm

☐ Soft (Std.) ☒ Hard

Rear Sus. Bush
☐ Short
☐ Medium
☒ Long



Servo Horn

Steering	Throttle
☐ Plastic	☐ Plastic
☐ AL. Long	☒ AL.
☒ AL. Short	

Steering Plate



Sway Bar



Front	Rear
φ 2,3mm	φ 2,9mm
1 mm	2 mm

Weight

Front	Rear
☐ None	☐ None
☐ IFW604-10	☐ IFW605-10
☒ IFW604-20	☒ IFW605-20
☐ other	☐ other

Wing

☒ IF491(TKI4)

Flap ☒ None
☐ 5mm
☐ 8mm
☒ Holes



memo:

OPTIONS:
- titanium screws and turnbuckles
- IFW426 aluminium AMB Plate
- IFW436 16 degrees caster blocks
- IFW631 and IFW632 shock towers
- IFW626 carbon servo saver plate
- IFW613 front CVA driveshafts
- rear hub position and hexes for legal width on AKA wheels