

Name of Driver		Date	Track		Engine	Plug	Muffler	
Renaud Savoya		08/01/22	IBR Padova		Picco P3TT	P5TH	EFRA 2166	
		Condition: Slippery Temperature: 2°C						
Spur Gear	Clutch Bell	Clutch Spring	Clutch Shoe	Tire	Tire Insert	Wheel	Body	Fuel
45 T	☐ Std. ☒ LW 1 T	☐ 0.90 ☐ 1.00 ☒ 0.95 ☐ 1.10	Carbon ☒ 3 Aluminum ☒	Tire : AKA Typo Compounds: S	AKA	Kyosho soft	TKI2	Hot Road GT

● Diff. Gear Set-Up

	Front	Center	Rear
Diff. Gear	☒ 10/20 ☐ 12/18 ☐ LSD Ring Gear ☒ 43/13 ☐ 42/12	☒ 10/20 ☐ 12/18 ☐ LSD Diff. Size ☒ Small ☐ Large	☒ 10/20 ☐ 12/18 ☐ LSD Ring Gear ☒ 43/13 ☐ 42/12
	# 10k	# 7k	# 10k

● Shock Set-Up

	Front	Rear
Shock Type	P : w/Diaphragm A : Aeration Size 50 - type P	Size 58 - type P
Shock Piston	B ϕ 5 x 1, 5 B : Black W : White T : Taper	B ϕ 5 x 1, 5
Shock Oil	# 650	# 400
Shock Spring	IFS001-751 5	IFS002-915

● Ride Height

Front	Rear
25 mm	28 mm

● Rebound

Front	Rear
102 mm	12 mm 4

● Camber Angle

Front	Rear
+ 2 °	+ 2 °


● Toe Angle

Front	Rear
+ 2 °	☐ 2.5° ☒ 3° ☐ 3.5°

● Wheelbase


Collar of Rear Hub	Front Side 2 mm Rear Side 3 mm
--------------------	-----------------------------------

● Shock Mount Position



Sus. Arm	Front ☐ In ☐ Out Rear ☐ In ☒ Out
----------	--

● Rear Upper Arm Position



● Rear Wheel Hub

☐ Narrow ☒ Std. ☐ Wide
--

Shock Stay

Front	☐ Short ☒ Long ☐ Alu ☒ Carbon
Rear	☐ Short ☒ Long ☐ Alu ☒ Carbon

Shock Bush

Front	☐ Short ☐ Std. ☐ Long
Rear	☐ Short ☐ Std. ☐ Long

☐ Plastic ☒ Aluminum
--

Hub Carrier Bush	☒ Plastic ☐ Brass
------------------	---

☐ Narrow ☒ Std. ☐ Wide
--


● Front Sus. Arm

☐ SS ☒ Soft (Std.) ☐ Hard

● Front Sus. Bush

Rear Side	☐ ☒
-----------	--

● Front Upper Arm Position




● Front Wheel Hub

☐ Narrow ☒ Std. ☐ Wide
--

● Front Hub Carrier

☐ Plastic ☒ Aluminum
☐ 13° ☐ 16° ☒ 17.5° ☐ 19° ☐ 22°



● Rear Sus. Bush

Front Side	☐ ☐ ☐ ☐
Rear Side	☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐

● Rear Sus. Arm


☐ Soft (Std.)	☐ Hard
Rear Sus. Bush	
☐ Short	☐
☐ Medium	☐
☐ Long	☐

A detailed technical drawing of a rear suspension bush. It features a central cylindrical hole with a smaller inner bore. A cotter pin is inserted through the center, with its ends extending outwards. The bush has a flange on one side and a tapered end on the other.

● Servo Horn

Steering	Throttle
☐ Plastic ☐ AL. Long ☐ AL. Short	☐ Plastic ☐ AL.

● Steering Plate



● Sway Bar

Front	Rear
ϕ 2,3mm 0 mm	ϕ 2,8mm 2 mm

● Weight

Front	Rear
☐ None ☒ IFW604-10 ☒ IFW604-20 ☐ other	☐ None ☐ IFW605-10 ☒ IFW605-20 ☐ other x2 = 40g

● Wing

☒ IF491(TKI4)	Flap ☒ None ☐ 5mm ☐ 8mm ☒ Holes
---	--

memo: