

InfernoMP10 SET UP SHEET

ver.1.01

KYOSHO
THE FINEST RACE CONTROL MODEL

Name of Driver		Date	Track		Engine	Plug	Muffler	
Reno Savoya		06/07/20	A2 Tech Sens Condition: High grip		Picco P3TT	Picco #5	Picco 2166	
Spur Gear	Clutch Bell	Clutch Spring	Clutch Shoe	Tire	Tire Insert	Wheel	Body	Fuel
46 T	☐ Std. ☒ LW 13T	☐ 0.90 ☐ 1.00 ☒ 0.95 ☐ 1.10	Carbon ☒ Aluminum ☒ 3	Tire : Impact Compounds: MLW	AKA red	AKA	stock	Hot road GT

● Diff. Gear Set-Up

	Front	Center	Rear
Diff. Gear	☐ Std. ☐ LSD Ring Gear ☒ 43/13 ☐ 42/12 # 20k	☐ Std. ☐ LSD Ring Gear ☒ 43/13 ☐ 42/12 # 10k	☒ Std. ☐ LSD Ring Gear ☒ 43/13 ☐ 42/12 # 10k
	IFW621	IFW622	IFW621

● Shock Set-Up

	Front	Rear
Shock Type	P : w/Diaphragm A : Aeration Size P - type stock	Size P - type stock
Shock Piston	B : Black W : White T : Taper T φ 1,2 x 8	T φ 1,4 x 8
Shock Oil	# 500	# 600
Shock Spring	Blue (IFS001-715)	Blue (IFS002-815)

● Ride Height

Front	Rear
22 mm	28 mm

● Rebound

Front	Rear
110 mm	125 mm

● Camber Angle

Front	Rear
+ -2 °	+ -2 °

● Toe Angle

Front	Rear
+ -2 °	☒ 2.5° ☐ 3° ☐ 3.5°

● Wheelbase

Collar of Rear Hub	Front Side 3 mm Rear Side 2 mm
--------------------	-----------------------------------

● Shock Mount Position

<Front>	<Rear>	Rear Upper Shock Bush ☐ Std. ☒ Long
		Sus. Arm Front ☐ In ☒ Out Rear ☐ In ☒ Out

● Rear Upper Arm Position

	☐ Plastic ☒ Aluminum	Hub Carrier Bush ☒ Plastic ☐ Brass
	☐ Narrow ☒ Std. ☐ Wide	


● Front Sus. Arm

☒ Soft (Std.) ☐ Hard

● Front Sus. Bush

Rear Side	☒
-----------	-------------------------------------

● Front Upper Arm Position




● Front Wheel Hub

☐ Narrow ☒ Std. ☐ Wide
--

● Front Hub Carrier

☐ Plastic ☒ Aluminum
☐ 13° ☒ 16° ☐ 17.5° ☐ 19°



● Front Wheel Hub

Lower Bush

☒ Plastic
 ☐ Brass

☐ -1°
 ☒ 0°
 ☐ +1°





● Rear Sus. Bush

Front Side	☐
Rear Side	☒


● Rear Sus. Arm

☒ Soft (Std.) ☐ Hard
Rear Sus. Bush
☐ Short ☐ Medium ☒ Long

● Servo Horn

Steering	Throttle
☐ Plastic	☐ Plastic
☒ AL. Long	☒ AL.
☐ AL. Short	

● Steering Plate



● Sway Bar

Front	Rear
φ 2,3mm	φ 2,8mm
1 mm	1 mm

● Weight

Front	Rear
☐ None	☒ None
☐ IFW604-10	☐ IFW605-10
☒ IFW604-20	☐ IFW605-20
☐ other	☐ other

● Wing

☒ IF491(TK14)	Flap ☒ None
	☐ 5mm
	☐ 8mm
	☒ Holes

memo:

Options on setup sheet plus:

- titanium screws IFW602
- new diffs IFW621 and IFW622
- aluminum AMB plate IFW426
- rear center dogbone IFW616 and IFW617
- new towers and longer shocks (IF484, IS215, IFW623, IFW624)