

Name of Driver		Date	Track / Event		Engine	Plug	Manifold	Muffler
		06/2023	Basic setup no option					
		Condition:		Temperature: 25°C				
Spur Gear	Clutch Bell	Clutch Spring	Clutch Shoe	Tire	Tire Insert	Wheel	Body	Fuel
☐ 0.8 ☒ 1.0 46 T	☐ 0.8 ☒ 1.0 13 T	☐ 0.90 ☒ 1.00 ☐ 0.95 ☐ 1.10	Carbon ☒ X Alu. IFW636 ☒ X 3	Tire : _____ Compounds: _____			TK13	

● Diff. Gear Set-Up

	Front	Center	Rear
Diff. Gear	☒ 10/20 ☐ 12/18 ☐ LSD	☐ 10/20 ☒ 12/18 ☐ LSD	☒ 10/20 ☐ 12/18 ☐ LSD
	Ring Gear ☒ 43/13 42/12	Diff. Size ☒ Small ☐ Large	Ring Gear ☒ 43/13 42/12
	7 000 #	20 000 #	3 000 #

● Shock Set-Up

	Front	Rear
Shock Type	P : w/Diaphragm A : Aeration	
Shock Piston	B : Black W : White T : Taper	
Shock Oil		
Shock Spring		

Size 50 P type 58 P

W: 5x1,4mm B: 5x1,5mm

650 # 650

72mm black 86mm black


● Ride Height

Front	Rear
24 mm	28 mm

● Camber Angle

Front	Rear
-2°	-2°
mm	mm

● Rebound




Front	Rear
106 mm	123 mm

● Plate

Front	☐ Aluminum ☐ Carbon ☒ Plastic
Center	☒ Aluminum ☐ Carbon
Radio	☒ Aluminum ☐ Carbon
AMB	☒ Aluminum ☐ Carbon ☐ Plastic



● Front Toe Angle




● Shock Stay

Front	☐ Short ☒ Long
	☒ Alu. ☐ Carbon
Rear	☐ Short ☒ Long
	☒ Alu. ☐ Carbon

Shock Bush	
Front	☐ Short ☒ Std.
Rear	☐ Short ☒ Std. ☐ Long

● Steering Plate



● Servo Horn

Steering	Throttle
☒ Plastic	☒ Plastic
☐ Alu. Long	☐ Alu.
☐ Alu. Short	

● Wing

Flap	☒ None ☐ 5mm ☐ 8mm
Spacer	☐ None ☐ 2.5mm ☐ 5mm ☒ 7.5mm ☐ Other _____ mm
Holes	

● Front Sus. Arm

☒ SS ☐ Soft ☐ Hard

● Front Sus. Holder

☒ Aluminum ☐ Steel

● Front Sus. Holder Bush

Rear Side ☒ ☐ ☐


● Front Wheel Hub

☐ Narrow ☒ Std. ☐ Wide

● Front Hub Carrier

☒ Plastic ☐ Aluminum

☐ 13° ☐ 16° ☒ 17.5° ☐ 19° ☐ 22°



● Rear Sus. Holder Bush

Front Side	☐ ☐ ☒ ☐
Rear Side	☐ (2) (2) ☐ (2.5) (2.5) ☒ (3) (3) ☐ (3.5) (3.5) ☐ (2) (2) ☐ (2.5) (2.5) ☐ (3) (3) ☐ (3.5) (3.5)

● Rear Sus. Arm


☒ Soft ☐ Hard

Rear Sus. Bush

☐ Short ☐ Medium ☒ Long

● Sway Bar

Front	Rear
φ 2,4mm	φ 2,6mm
0 mm	2 mm



● Rear Wheel Hub

☐ Narrow ☐ Std. ☒ Wide

● Wheelbase

Collar of Rear Hub Carrier

Front Side _____ 5 mm


Rear Side _____ 0 mm

● Rear Hub Carrier

☒ Plastic ☐ Aluminum

Hub Carrier Bush

☒ Plastic ☐ Brass



● Shock Position of Sus. Arm

Front	☐ In ☒ Out
Rear	☐ In ☒ Out

● Center Drive Shaft

Front	☒ ☐
Rear	☒ ☐

● Universal Swing Shaft

Front	☒ Std. ☐ Cap-U
Rear	☒ Std. ☐ Cap-U

● Weight

Front	Rear
☒ None	☒ None
☐ IFW604-10	☐ IFW605-10
☐ IFW604-20	☐ IFW605-20
☐ other	☐ other

Memo :