

Name: _____ Date: _____ Event: _____ Ambient Temp: _____

Track: INDOOR OUTDOOR Size: SMALL MEDIUM LARGE Traction: LOW MEDIUM HIGH

Surface: SMOOTH BUMPY RUTTED Type: LOOSE / LOAMY HARD PACKED BLUE GROOVE CLAY ASTRO

Ackerman/Bumpsteer/Arm Plate/Spindle Height/Servo Saver Condition: DUSTY DRY WET MUDDY

WASHERS:

WASHERS:

WASHERS:

PLATE: **ABCDEFGHIJ**

SPINDLE PART#

TKR9141 (+1,0)

TKR9141B (-1, -2)

L H

FULL TURNS FROM FULLY TIGHT

(FRONT) (REAR) SWAY BAR BUSHINGS

Front End:

TOWER

UNI/CVD

U - TKR9087

C - TKR8072

STANDOFF

0mm +2mm +4mm

OFFSET

0mm 1mm 2mm

"A" Block:

TKR9161 (0mm)

TKR9161B (-1mm)

Suspension:

RIDE HEIGHT:	CAMBER:
CASTER BLOCK:	SWEEP:
KICK UP:	TOE:
SWAY BAR:	SHOCK LENGTH:
UP TRAVEL LIMITERS:	DROOP:
OIL:	BRAND:
PISTON:	SPRING:
REBOUND:	BUILD:

"B" Block:

TKR9162 (0mm)

TKR9162B (-1mm)

Differentials:

OPTION	FRONT	CENTER	REAR
Diff Oil			
(TKR5144B)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
(TKR5144)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
(TKR5145B)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
(TKR9145)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Standard (TKR9114-TKR91)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Lightened (TKR5114XB-TKR5)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
(TKR9150)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
(TKR9150B)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
(TKR9115C)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
(TKR9115B)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
(TKR9149)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
(TKR9149A)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>

Rear End:

TOWER

UNI/CVD

U - TKR9087

U - TKR9287

U - TKR9287B

C - TKR8072

STANDOFF

0mm +2mm +4mm

REAR HUB

OFFSET

0mm 1mm 2mm

-2mm 0mm +2mm

REAR HUB

"C" Block:

TKR9163B (-1mm)

TKR9163C (-2mm)

Screw (TKR1324)

"D" Block:

TKR9164B (-1mm)

TKR9164C (-2mm)

Suspension:

RIDE HEIGHT:	CAMBER:
ANTI-SQUAT:	TOE:
SWAY BAR:	SHOCK LENGTH:
UP TRAVEL LIMITERS:	DROOP:
OIL:	BRAND:
PISTON:	SPRING:
REBOUND:	BUILD:

Chassis Braces:

REAR-SHORT: REAR-LONG:

Tires / Wheels:

BRAND / TREAD:
COMPOUND:
INSERT:
WHEEL:
NOTES:

Body / Wing:

BODY MAKE:
WING MAKE:
WING MOUNT POSITION:
0mm: <input type="radio"/> +7mm: <input type="radio"/>
NOTES:

Bulkheads:

FRONT

TKR9416 (0mm)

TKR9416B (-2mm)

REAR

TKR9416 (0mm)

TKR9416B (-2mm)

Drivetrain:

CLUTCH / SPUR:	/	(teeth)
CLUTCH SHOES/SPRINGS:	/	
BRAKE BIAS %:	(front)	(rear)

Engine/Electronics

ENGINE / PIPE:	/
FUEL / PLUG:	/
STEERING	THROTTLE / BRAKE
SERVO:	/

Notes:

Wheelbase:

REAR FRONT

(Shims)

(Thick - 2mm)

(Thin - 1mm)