

SET-UP SHEET

XRAY XB8'25 SET-UP VER.01 ©XRAY

XRAY XB8'25 PIVOT BALL

RACE		
TRACK		
NAME		DATE

TEMPERATURE AIR		TEMPERATURE TRACK	
LAPS		BEST LAPTIME	
FINAL POSITION		RACE LENGTH	
		/sec	/min

TRACKS			
SIZE	☐ OPEN	☐ MEDIUM	☐ TIGHT
TRACTION	☐ LOW	☐ MEDIUM	☐ HIGH
SURFACE	☐ SMOOTH	☐ MEDIUM	☐ BUMPY
TYPE	☐ HARD PACKED	☐ SOFT DIRT	☐ CLAY
	☐ BLUE GROVE	☐ ASTRO TURF	☐ GRASS
CONDITION	☐ DRY	☐ DUSTY	☐ WET
	☐	☐	☐ MUD

DIFFERENTIAL			
FRONT		CENTER	REAR
CASE MATERIAL			CASE MATERIAL
OIL			OIL
CROWN GEAR			CROWN GEAR
PINION	13 ☐ 14 ☐		PINION

GEARING	
CLUTCH SHOE	3 ☐ 4 ☐
SPRINGS	
CLUTCH BELL	/T
SPUR GEAR	/T

FRONT	SHOCKS	REAR
	TYPE	
	SPRINGS	
	MEMBRANE	
	OIL	
	/cSt	/cSt

STANDARD PISTONS			
☐ 6 HOLES	☐ 1.1 mm	☐ 6 HOLES	☐
☐ 8 HOLES	☐ 1.2 mm	☐ 8 HOLES	☐
☐ 10 HOLES	☐ 1.3 mm	☐ 10 HOLES	☐
☐	☐ 1.4 mm	☐	☐
☐	OTHER	☐	☐
VALVE PISTONS			
☐ 5+2 HOLES	☐ 1.5 mm	☐ 5+2 HOLES	☐
☐ 6+2 HOLES	☐ 1.3 mm	☐ 6+2 HOLES	☐
☐ 8+2 HOLES	☐ 1.4 mm	☐ 8+2 HOLES	☐
☐	☐ 1.2 mm	☐	☐
☐	☐ 1.3 mm	☐	☐

FRONT	ANTI-ROLL BAR	REAR
	THICKNESS	
	/mm	/mm

FRONT	TIRES	REAR
	BRAND	
	COMPOUND	
	INSERTS	
	WHEELS	

ENGINE	
TYPE	
MUFFLER	
MANIFOLD	
PLUG	
FUEL	

BODY	OTHER	TOTAL WEIGHT
EASY ☐ EASY LIGHT ☐		/g

FRONT	REAR
STEERING BLOCK MEDIUM ☐ HARD ☐ GRAPHITE ☐	UPRIGHT MEDIUM ☐ HARD ☐ GRAPHITE ☐ ALU #350908 ☐
UPPER ARM SHIM /mm 0 ☐ 1 ☐ 1.5 ☐ 2 ☐	ANTI-ROLL BAR 1 2 ☐ 1 2 ☐
UPPER ARM WING NONE ☐ LEXAN ☐ CARBON ☐	UPPER SHOCK POSITION 1 2 3 4 ☐ 1 2 3 4 ☐
PIVOT BALLS UP STEEL ☐ ALU ☐ DOWN STEEL ☐ ALU ☐	FLAT ☐ LSM ☐
FRONT OFFSET 0 +1 +2 +3 +4 ☐	STD. ☐ 2 DOTS ☐
PIVOT NUT ALU ☐ BRASS ☐	GRAPHITE ☐ KIT ☐
FRONT LOWER SHOCK POSITION 2 1 ☐ 2 1 ☐	REAR OFFSET 0 +1 +2 +3 +4 ☐
LOWER ARM SHIM /mm 0 ☐ 1 ☐ 2 ☐	STD. ☐ 2 DOTS ☐
FRONT DROOP MEASURE UNDER WHEEL AXLE #10717 GAUGE	REAR DROOP MEASURE UNDER WHEEL AXLE #10717 GAUGE

FRONT	REAR
UPPER ROLL CENTER 1° ☐ 0.5° ☐	REAR WING COMPOSITE ☐ LEXAN ☐ OTHER ☐
CASTER SHIM 0 1.0 1.0 2.0 ☐	CUT OUT HOLES FRONT ☐ MIDDLE ☐ REAR ☐
BUMP STEER SHIM STER. PLATE /mm STER. BLOCK /mm SHIMS PLACE ALWAYS UNDER	CARBON BRACE WITHOUT ☐ 1-PIECE ☐ 2-PIECES ☐
WHEELBASE SHIM POSITION 0mm 2mm 4mm ☐	WHEELBASE SHIM POSITION 0mm 2mm 4mm ☐
LOWER ROLL CENTER ECCENTRIC BUSHINGS FRONT ☐ REAR ☐	RF ☐ RR ☐

FRONT	REAR
FRONT TOE OUT STEERING PLATE CARBON ☐ ALU ☐ 1 DOT ☐ 2 DOTS ☐ 3 DOTS ☐	REAR TOE IN #355215 ADJ. DRIVE AXLE
CHASSIS KIT ☐ LONG +4mm ☐	WHEELBASE 0mm 1mm 2mm 3mm 4mm ☐
FRONT DRIVE SHAFT CVD ☐ UNIVERSAL ☐ LENGTH /mm	REAR DRIVE SHAFT CVD ☐ UNIVERSAL ☐ LENGTH /mm
TOP DECK COMPOSITE ☐ CARBON ☐	SIDE GUARD SOFT ☐ MEDIUM ☐ CARBON ☐
ACKERMANN POSITION 4 3 2 1 ☐	REAR DRIVE SHAFT CVD ☐ UNIVERSAL ☐ LENGTH /mm
SERVO SAVER TIGHT ☐ MEDIUM ☐ SOFT ☐	DRIVE SHAFT CVD ☐ DOGBONE ☐
DRIVE SHAFT CVD ☐ DOGBONE ☐	DIFF PLATE COMP. ☐ CARBON ☐

FRONT	REAR
FRONT CAMBER LENGTH mm	REAR CAMBER LENGTH mm
UPPER ARM SOFT ☐ MEDIUM ☐ GRAPHITE ☐	FRONT DIFF HEIGHT 1 2 3 4 ☐
LOWER ARM SOFT ☐ MEDIUM ☐ GRAPHITE ☐	REAR DIFF HEIGHT 1 2 3 4 ☐
RIDE HEIGHT /mm	RIDE HEIGHT /mm