



Name:	, • • • • • • • • • • • • • • • • • • •	Date:		Event:				
Track: INDOOR O	utdoor O Size:	SMALL O MEDIUM O	LARGE O	Traction: L	OW O MEI	ошм С	HIG	нО
Surface: smooth •	BUMPY O RUTTED O	Type: Loose/Lo	DAMY O HARD PAG	CKED O BLUE GF	ROOVE O	LAY O	ASTR	O
Ackerman/Bumpsteer/	Arm Plate/Spindle He	ight/Servo Saver	Condition:	DUSTY O D	RY O WE	т О	MUDD	Y O
00	- 1	WASHERS:		L #		29		ULL JRNS
. ! !	WASHERS:	A B C		$\Diamond \Diamond \blacksquare$		ET [☐ FI	ROM ULLY
-		PLATE OF		. 1 =	7.66	r .		GHT
Front	End:	Suspe	nsion:	OF	Differe	ntials FRONT :		REAR
00	UNI/CVD	RIDE HEIGHT:	CAMBER:		0il □>			HE/III
		CASTER BLOCK: KICK UP:	SWEEP: TOE:	(TKR5144B				_
00	OFFSET OFFSET	SWAY BAR:	DROOP:			0	0	0
	1r	mm	ocks:	(TKR5144)		0	0	0
		OIL:	BRAND:	(TKR5145B	9	0	0	0
		PISTON:	SPRING:	(TKR9145)	•	0	0	0
		REBOUND:	BUILD:	Standard		0	0	0
	"Block:	- 00	"B" Block:	(TKR9114-TKR: Lightened		0	0	0
	TKR9161 (0mm)		TKR9162 (0mm)	(TKR5114XB-TKI	R5112x)			
8	TKR9161B (-1mm)		TKR9162B (-1mm	(TKR9150)		0	0	0
Rear	End:	Suspe	nsion:	(TKR9150B		0	0	0
	UNI/CVD	RIDE HEIGHT:	CAMBER:	(TKR9115)		0	0	0
	P ≥= ≥8	U <u>Anti-squat:</u> C	TOE:	(TKR9115B		0	0	0
	REAR HUB OFFSI		DROOP:					_
AAA		Omm Sho 1mm	cks:	(TKR9149)	70	0	0	0
	<u>am</u> 0	^{2mm} OIL:	BRAND:	(TKR9149A	· +	0	0	0
		PISTON: REBOUND:	SPRING: BUILD:	_	Drivet	rain:		
				CLUTCH / SPUF	R:	/	(teeth)
			is Braces:	CLUTCH SHOES				
COD.	REAR HUB LRC HRC	REAR-SHORT: O	rear-long: O / Wheels:	CLUTCH SPRING BRAKE BIAS %		ont)		(rear)
	"C" Block:	BRAND/TREAD:	WIICCIS.		ngine/Ele			(Teal)
Screw O >	TKR9163B (-1mm)	COMPOUND:		ENGINE / PIPE:	:	/		
(TKR1324)	TKR9163C (-2mm)	INSERT:		FUEL / PLUG:		<u>/</u>		
	"D" Blasky	WHEEL:		RX BATTERY:	STEERING	THRO	OTTLE / BF	RAKF
	"D" Block:	NOTES:	//Wing:	SERVOS:	37EEMING	/	JITEE, DI	UIKL
	TKR9164B (-1mm) TKR9164C (-2mm)	BODY MAKE:	y/Wing:		Not	es:		
Wheelbase:		WING MAKE:		_				
	(Shims)	WING MOUNT POSITION:						
REAR FRO	(Thick - 2mm)	0mm:	m: O + 12mm: C					
INLAIN THE FRU	N (Thin - 1mm)							